



## Reference 12


The Reference 12 is a high-performance powered point source speaker engineered for exceptional clarity and adaptability. Designed for professional booth or stage monitoring, this medium-output coaxial model delivers superior sound reproduction in compact spaces while maintaining versatility for broader applications.

### Key Features:

- Coaxial design
- Built-in 3k watt amplification (Passive option Available)
- Variable Mounting Solutions
- Premium Integrated DSP w/ FIR Capabilities

### Applications:

- Stage Monitors
- DJ Booth Monitors
- Pop-up Stages
- Restaurant or Event Space Installation
- Wedding Events



## Specifications

**Frequency Response (-3 dB):** 65 Hz - 20 kHz

**Frequency Response (-10 dB):** 50 Hz - 20 kHz

**Dispersion Pattern (Horizontal x Vertical):** 80° x 80°

**Weight:** 44 lbs

**Connections:** 2 x XLR (Input/Output) or 2 x NL4

**Dimensions (W x H x D):** 16.375" x 23.25" x 16"

## Driver Specification

Driver	Crossover Frequency	Power (Nominal, Continuous)	Driver Impedance	Nominal Impedance	Sensitivity (1w/1m)	Pinouts
12" HF	1.3 kHz - 20kHz	80 W, 160 W	8Ω	8Ω	106 dB	1+, 1-
12" LF	40 Hz - 1.3 kHz	500 W, 1000 W	8Ω	8Ω	100 dB	2+, 2-